IN THE CLAIMS

Kindly amend claims 6 and 7 as shown in the following claim listing:

- 1. (original) A multi-stack optical data storage medium (20) for rewritable recording using a focused radiation beam (19) entering through an entrance face (16) of the medium (20) during recording, comprising:
 - -a substrate (1) with deposited on a side thereof:
- -a first recording stack (2) L_0 comprising a first phase-change type recording layer (6), said first recording stack (2) being present at a position most remote from the entrance face (16),
- -at least one further recording stack (3) L_n , which comprises a further phase-change type recording layer (12), being present closer to the entrance face (16) than the first recording stack (2),
- -a transparent spacer layer (9) between the recording stacks (2, 3), said transparent spacer (9) layer having a thickness larger than the depth of focus of the focused laser-light beam (19),
- characterized in that the further recording layer (12) is substantially of an alloy defined by the formula $Ge_xSb_yTe_z$ in atomic

percentages, where 0 < x < 15, 50 < y < 80, 10 < z < 30 and x + y + z = 100 with a thickness selected from the range of 4 to 12 nm and that at least one transparent crystallization promoting layer (11', 13') having a thickness smaller than 5 nm is present in contact with the further recording layer (12).

- (original) An optical storage medium (20) as claimed in claim
 , wherein the transparent crystallization promoting layer (11',
 mainly comprises a material selected from the group of nitrides, oxides of Si, Al and Hf.
- (original) An optical storage medium (20) as claimed in claim
 wherein the transparent crystallization promoting layer (11',
 mainly comprises a material selected from the group of
 nitrides of Al and nitrides of Si.
- (original) An optical storage medium (20) as claimed in claim
 , wherein the further recording layer (12) has a thickness selected from the range of 4 to 8 nm.
- 5. (original) An optical storage medium (20) as claimed claim 1, wherein the alloy has a composition defined by the formula $Ge_xSb_yTe_z$

in atomic percentages, where 5 < x < 8, 70 < y < 80, 15 < z < 20 and x + y + z = 100.

- 6. (currently amended) An optical storage medium (20) as claimed in any one-of-claims claim 1, wherein a metal reflective layer (14), semi-transparent for the radiation beam (19), is present in the further recording stack (3).
- 7. (original) An optical storage medium (20) as claimed in $\frac{1}{2}$ claims 6, wherein the metal reflective layer (14) mainly comprises the element Cu.
- 8. (previously presented) Use of an optical storage medium (20) as claimed in claim 1, for high speed recording with a recording speed higher than 12 m/s.